

# FINISHING MACHINE



☞ **Figure Finisher**

☞ **Spot Table**

☞ **Ironing Table**

☞ **Laundry Press**

RELIABILITY DURABILITY COST EFFECTIVE

## FIGURE FINISHER

- ☐ The figure finisher consists of the frame, pressing structure, electrical box, the unit complete and pedal switch. It can finish the western-style clothes, garment, sweater and skirt. It is necessary for clothes factory, hotel, hospital and laundry store.
- ☐ Controlled by DLC computer, and also can be manual control. With special designed working procedure, no matter how thick, how complicate the garment is, you'll be satisfied with the ironing quality.
- ☐ Designed with wind pressure, shoulder width, waist, hipline, lap and fly height adjuster. It is able to press small size garment like woman clothes.
- ☐ Professional design of steam circuit, which assures the quality of steam spray.

### Specification for Figure Finisher

| Model No.         | Unit   | ZTR           |
|-------------------|--------|---------------|
| Steam pressure    | Mpa    | 0.3~0.5       |
| Steam consumption | Kg/h   | 15~20         |
| Power supply      | V/P/Hz | 380/3/50      |
| Motor power       | Kw     | 0.75          |
| Dimension         | mm     | 1600×560×1080 |
| Net weight        | Kg     | 140           |



XYLECATALOGUE2014-0516

## SPOT TABLE

- The dirty spot on the garment can be treated on the spot table with the help of special cleanser. The dirt such as lipstick, paint smudge, blood, ink, coffee and milk should be removed easily.
- A jet gun and tow dirt removing guns are provided. The jet gun can be applied to the garment either in cold or hot according to the dirt type.
- Equipped with spot-removing gun and hot wind gun, and the gun is suitable to your hands. The fluid is concentrate. Touch style button is very sensitive and convenient.
- Equipped with a set of air filter, which prevent the second pollution to garments. Hot wind and steam are controlled by magnetic valve, which can fully utilize the eradicator and strengthen spot-removing effect.
- Equipped with stainless steel table



### Specification for Spot Table

| Model No.               | Unit | QZ-A         |
|-------------------------|------|--------------|
| Steam pressure          | Mpa  | 0.4~0.5      |
| Compressed air pressure | Mpa  | 0.5~0.6      |
| Power supply            | V/Hz | 220/50       |
| Motor power             | Kw   | 0.25         |
| Dimension               | mm   | 1400×560×900 |
| Net weight              | Kg   | 60           |

## IRONING TABLE

- Air-sucking ironing table is widely used in finishing the polyester-fiber, cotton and sweaters.
- It works with strong sucking and minimal noise, with steam iron.
- Beautiful design, easy operation and ideal ventilation system can meet your requirement.



### Specification for Ironing Table

| Model No.       | Unit   | YTTB2    |
|-----------------|--------|----------|
| Suction         | Pa     | 150      |
| Power supply    | V/P/Hz | 380/3/50 |
| Motor power     | Kw     | 0.55     |
| Table dimension | mm     | 1500×800 |
| Net weight      | Kg     | 50       |



Multipurpose Press



Omnipotent Press



Collar-sleeve Press



Mushroom Press

## LAUNDRY PRESS

- The press consists of bottom seat, frame, operate station, upper ironing table, lower ironing table, pneumatic steam valve, pedal switch, cylinder and spring assembly.
- It is suitable for ironing all kinds of garments.
- It is the best selection for hotels, hospitals, laundry stores and clothes factories.
- Be able to press just after cloth dehydrated.
- Using high-quality pneumatic components and with reasonable designed steam circuit. It is stable, reliable and safe.
- Steam Road, concise design effective, warming fast, low heat loss.

### Specification for Laundry Press

| Name                    | Unit   | Multipurpose Press | Omnipotent Press | Collar-sleeve Press | Mushroom Press |
|-------------------------|--------|--------------------|------------------|---------------------|----------------|
| Model No.               |        | ZJW                | ZJWB             | ZJWC                | ZJWD           |
| Purpose                 |        | dry cleaning       | wet cleaning     | wet cleaning        | wet cleaning   |
| Steam pressure          | Mpa    | 0.4~0.5            | 0.4~0.5          | 0.4~0.5             | 0.4~0.5        |
| Steam consumption       | Kg/h   | 25                 | 25               | 20                  | 15             |
| Compressed air pressure | Mpa    | /                  | 0.4~0.5          | 0.4~0.5             | 0.4~0.5        |
| Power supply            | V/P/Hz | 380/3/50           | 380/3/50         | 380/3/50            | 380/3/50       |
| Dimension               | mm     | 1200×1400×1400     | 1350×1400×1300   | 1200×1400×1300      | 1200×1400×1330 |
| Net weight              | Kg     | 250                | 260              | 230                 | 220            |

All specifications subject to change without notice.

Shandong LittleDuck Group Co., Ltd.  
 Add: Gongye Nan Road, Jinan, Shandong, 250101 China  
 Tel: 0086-531-8312 2094, 8312 2068  
 Fax: 0086-531-88681524  
 Website: www.littleduckgroup.com.cn